ULTRAFLEX SYSTEMS INCORPORATED

Technical Data Sheet

SuperSmooth™ PET GreyBack

SuperSmoothÊ PET GreyBack is a 13 oz. non-curling banner with a super smooth print surface and a grey back. The material is ideal for high resolution printing. The grey back-side prevents light transparency and shadowing. SuperSmooth PET GreyBack is ideal for pop-up, roll-up, x-displays and an array of close viewing indoor applications. The material does not require lamination and is available in a matte finish. SuperSmooth PET Greyback is compatible for use with solvent, eco-solvent, UV and screen printing. Available in widths from 38ò- 126ù

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Support Cloth	DIN ISO 2076	Polyethylene terephthalate	
Yard dtex	DIN EN ISO 2060	N/A	N/A
Total Weight	DIN EN ISO 2286-2	450 g/m^2	13 oz/yd^2
Tensile Strength	GB/T10403-2006	1288 x 1492 N/5cm	147.08 x 170.38lbs/inch
Tear Strength (warp/weft)	HG/T2581-1994	3.6 x 3.5 N/5cm	0.41 x0.39 lbs/inch
Fire Resistance	NFPA701		

Applications

	Pop-Up Displays	Banner	Roll-Up Displays	Blockout	Scrolling Signs	X-Displays	Trade Show Displays
Applications	■	■	■	■	■	■	■

Ink Printability

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct
■	■	■		■		

Available Sizes

Metric (m)	English (inches)
0.965, 1.37, 1.60, 2.03, 3.20	38ù 54ù 63ù 80ù 126ò

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

ULTRAFLEX SYSTEMS INCORPORATED
www.ultrafleXX.com
updated: 7/2015

Ultraflex Headquarters
1578 Sussex Turnpike, Bldg 4
Randolph, NJ 07869
P: (973)627-8608
Email: sales@ultraflexx.com

Ultraflex Europe
Unit 1 Hardwick Road Industrial Park
Great Gransden Bedfordshire
England SG19 3BJ
Phone: (44)1767-677-100
Email: sales@ultraflexeurope.com

Ultraflex México
Azafrán No. 112, Col.Granjas México
Del. Iztacalco, C.P. 08400, México D.F.
Tel: (55)31823632,3182 3608
01 800 822 52 31
Email: sales.mx@ultraflexx.com

Ultraflex Guadalajara
Av. Patria No. 2804
Loma Bonita Sur.
Zapopan, Jalisco CP45086
Mexico
Tel: (55)3312-049-857