

ROLLSROLLER® REGULAR 400/145R



KEY FEATURES

- Standard model with illumination (LED) and storage trays
- Wide range of options
- Ergonomic traverse

ROLLSROLLER Regular is our standard model and the perfect match for many.

It arrives fully assembled for a quick and easy start. With a welded frame of steel, this machine will be faithful to you and give you perfect results for many years.



MODEL NAME	ROLLSROLLER® 400/145R
Model type	Regular
Bed length	4 000 mm / 13ft. 2in.
Bed width	1 450 mm / 4ft. 9in.
Length of working area	3 700 mm / 12ft. 2in.
Width of working area/roller width	1 400 mm / 55in.
Overall width incl. Glide beam	1 685 mm / 5ft. 7in.
Overall height incl. Glide beam	1 400 mm / 4ft. 7in.
Max. thickness of substrate	60 mm / 2 2/5in.
Work height flatbed	875 mm / 2ft. 10in.
Bed surface	Glass + Cutting mat
Power Supply (if illuminated)	230V/50Hz (10A) /120V/60Hz (15A)
Required air pressure	6-8 bar / 87-116 psi
Weight	490 kg / 1080 lb
Packing weight, (total: pallet + machine)	800 kg / 1763 lb
Packing weight, (total: pallet + Crates + machine)	940 kg / 2072 lb
Packing dimension	4 100 x 2 000 x 1 800 mm / 13ft. 5in. X 6ft. 7in. X 5ft. 11in.
Warranty	2 years
Owner's Manual (Bruksanvisning i Original)	DA, DE, ENG, ES, FR, SV
Light table (LED)	yes
Roll holder for Glide Beam	yes
Roll holder for bed end	yes
Wheels	yes (4)
Storage trays	yes
Stop static kit, cord and magnet	yes
Additional roll holder on short side	option
Height adjustment	option
Antistatic system	option
Extra glidebeam	option
Air blow gun	option

ROLLSROLLER®
FLATBED APPLICATOR

info@rollsroller.se
rollsroller.se
+46 54 770 70 10

Patented product developed and manufactured by ROLLSROLLER AB in Sweden.

