ProtecRite®

8510

Product Design

ProtecRite 8510 is a 3mil UV stable co-extruded polyolefin film with a solvent rubber adhesive system. This adhesive system offers uniform adhesion over a variety of surfaces and can be applied over partially cured paints and coatings.

Application

ProtecRite 8510 is a sign protection film that will help eliminate damage during fabrication, storage, shipping, and installation.

Performance Features

- ☑ Co-extruded film backing **withstands fabrication** processes
- ☑ Solvent rubber adhesive resists build and **removes cleanly**
- ☑ Outdoor durable film that is **UV resistant** up to 6 months

Physical Properties	Values
Colors	Blue
Nominal Thickness	3 mils (.08 mm)
Adhesion (@90°)	11 oz/in (3.0 N/25mm)
Tensile Strength	11 lb/in (48 N/25mm)
Elongation (%)	450

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be constructed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Biltrite assumes no liability for claims beyond the replacement value of our product proved to be defective.

Cv8510/0614signs

FM 26197

AMERICAN BILTRITE INC.
105 Whittendale Drive, Moorestown, NJ 08057 • Phone: (856) 778-0708
Toll Free Fax: (888) 224-6325 • Website: www.abitape.com • Email: info@abitape.com