ProtectRite®

6560

Product Design

ProtectRite (6560) is a high grade, printable saturated fibrous paper backing with a specially formulated latex pressure sensitive adhesive system.

Application

This product was designed for use in protecting highly polished surfaces such as polished stainless steel, painted steel, chrome plated steel and polished brass where a standard tack adhesive is required. This product is also used on mill finished and painted aluminum, specialty metals, synthetic marble, and glass. 6560 is also used for the protection of aluminum aircraft skin during forming and processing and can be used on plastic laminates, acrylic and polycarbonate sheeting.

Performance Features

- ☑ **Easily removable**, even over extended time periods
- ☑ One piece removal leaves surfaces **clean & stain-free**
- ☑ A specially designed adhesive system resists build, making for a **uniform adhesion**

Physical Properties	Values
Colors	White
Nominal Thickness	4 mils (0.10 mm)
Adhesion (@90°)	3 oz/in (.82 N/25mm)
Tensile Strength	20 lb/in (88 N/25mm)
Elongation (%)	3
Backing	Paper
Printable Surface	Yes

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be constructed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Biltrite assumes no liability for claims beyond the replacement value of our product proved to be defective.

Cv6560/0816

bsi. ISO 9001 Quality Management
FM 26197

PSTC RESPONSIBLE TAPE MANUFACTURER

ABI Tape

105 Whittendale Drive, Moorestown, NJ 08057 • Phone: (856) 778-0708
Toll Free Fax: (888) 224-6325 • Website: www.abitape.com • Email: info@abitape.com