Lacryl® Lacryl 800 Series

Lacryl 800 Series is an air dry acrylic lacquer designed specifically for screen process.



Features

Over 30 Standard Colors and over 3000 intermix colors.

Benefits

Provides the durability and fade resistance required for sign coatings.

Compatible Surfaces

- Polycarbonate
- Acrylics

Associated Products

- To adjust color intensity or saturation use extra ZZ208 or cut with 890 or 891 colorless.
- ZZ218 Retarder

MATTHEWS PAINT
Matthews Paint • Toll Free: 800.323.6593 • Fax: 800.947.0377
www.matthewspaint.com • 760 Pittsburgh Drive • Delaware, OH 43015

Product Information Effective 02/16
Part No. L8100 02/16
© 2016 Matthews Paint Company

Directions For Use

Surface Preparation:
Apply over a clean surface free of dirt, lint, water, grease or oil.



Mix Ratios:
Lacryl 800 series is supplied ready to apply.

Reducers:
- ZZ208 as a thinner
- ZZ218 as a retarder



Application:
- Apply when air, product and surface temperature are above 50°F and at least 5° above dew point.
- Stir before use.



Drying Times:
- Minimum dry time before exposure to weather – 24 hours
- Air dry or force dry up to 150°F

Screen Cleaning:
ZZ205/ZZ208 or other suitable solvent

Factory Pack Colors:
- Over 30 standard colors
- Custom color matching available

Total Film Build:
Vary with silk screen mesh size.

Equipment:
Screen application

Equipment Cleaning:
Use ZZ205 or other suitable solvent.

Technical Data:
Lacryl L801 White

VOC	4.6 lb/gal
Solids	54% by wt
Wt/gal	9.7 lb/gal
Theoretical Coverage	1,600 sq. ft./gal @ 1 mil wet film

Important:
Before opening the packages, be sure you understand the warning messages on the labels of all components, since the mixture will have the hazards of all its parts. Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

See Material Safety Data Sheet and Labels for additional safety information and handling instructions.

Emergency Medical or Spill Control Information:
US (412) 434-4515; CANADA (514) 645-1320; Mexico 01-800-00-21-400

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to Matthews Paint. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does Matthews Paint warrant freedom from patent infringement in the use of any formula or process set forth herein. If you require technical assistance, please call us toll-free 800/323-6593.