Technical Data Sheet

Seaming Tape

Seaming Tape is a polyester scrim strip covered with a non-adhesive clear PVC. It is ideally used to combine/join smaller banners together to create one large graphic image. The product must be used with a heat or RF welder such as Miller Weldmaster or Leister. Machine settings are available on the Ultraflex website. Seaming Tape is available in three widths: 1.0ò 1.5òand 2.0ò

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Support Cloth	DIN 60001	PES Polyester	PES Polyester
Ends/Picks K/8 per cm	DIN 63853	4/4 per cm	10 x 13 per in
Yarn dtex K/S	DIN 53830	1000	1000
Greycloth-Weight g/m (rohw)	DIN 53854	185 g/m^2	5.5 oz/yd^2
Type of Coating		PVC	PVC
Total Weight g/m2	DIN 53352	400 g/m^2	10 oz/yd^2
Tensile Strength	DIN 53354	95 x 95 cm	200 x 190 in
Water Resistance	DIN 53363	360	360
RF Weldable		YES	YES

Available Sizes

English (inches)
1ò 1.5ò 2òwide

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

www.ultrafleXX.com
updated: 11/2014

Ultraflex Headquarters
1578 Sussex Turnpike, Building 4
Randolph, NJ 07869
P: (973)627-8608
Email: sales@ultraflexx.com

Ultraflex Europe
Unit 1 Hardwick Road Industrial Park
Great Gransden Bedfordshire
England SG19 3BJ
P: (44)1767-677-100
Email: sales@ultraflexeurope.com

Ultraflex México
Azafran No. 112, Col. Granjas México
Del. Iztacalco, C.P. 08400, México D.F.
P: (55)31823632, 3182 3608
Email: sales@mx.ultraflexx.com