Dynamic Plus

Gloss

TECHNICAL SPECIFICATION

Dynamic Plus Gloss is a 3.2 mil (80µ) monomeric soft calendared PVC laminating film with a glossy finish, coated on one side with a pressure sensitive acrylic adhesive that is protected by a Kraft release paper that is PE-coated on one side and siliconized on the release side.

- RECOMMENDED FOR INTERIOR AND EXTERIOR USE ON FLEXIBLE MEDIA SUBSTRATES WHERE A GLOSS FINISH IS REQUIRED
- IDEAL FOR POP DISPLAYS, ARCHITECTURAL RENDERINGS, PROMOTIONAL DISPLAYS, AND EVENT SIGNAGE

PRODUCT STRUCTURE

Film	Gloss Monomeric Soft Calendared PVC
Adhesive	Acrylic (Pressure Sensitive)
Release Liner	1 Side PE Coated, 1 Side Siliconized Kraft

PRODUCT CHARACTERISTIC

Film Thickness	3.2 mil (80µ)	4.2 mil (105µ)
Adhesive Layer	1 mil (25µ)	
Film/Adhesive Ratio	3.2:1	
UV Protection	Yes	
Outdoor Durability	2 Years	
Service Temperature Range	-4°F to 230°F (-20°C to 110°C)	
Shelf Life	2 Years	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

PROCESS SETTINGS

Equipment Type & **Temperature**	**Speed**
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

DRYTAC®
ADHESIVE SCIENCE

Europe
Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada
30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA
5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013