FloorTac™

Textures

ONE PART FLOOR GRAPHIC SOLUTION

FloorTac™ Textures is designed for vivid floor graphics that instantly take floors from drab to fab. Its removable, non-damaging adhesive makes FloorTac™ Textures ideal for short-term indoor advertising where graphics are applied to the floor. It is slip-rated and fire rated, making it ideal for public environments where safety is a top priority.

CAN BE APPLIED TO:

- SHORT PILE CARPETS
- CERAMIC TILES
- SEALED WOOD
- CONCRETE
- WAXED VINYL
- MARBLE, OR TERRAZZO

6.0 mil Textured White Polymeric PVC — Matte

(Eco)Solvent
Latex
UV

Removable
Gray Acrylic
(Pressure Sensitive)

Widths up to 54 in

MONTHS DURABILITY UP TO 6 **INTERIOR***





APPLICATIONS

SCHOOLS

HOSPITALS

RETAIL ADVERTISING

SUPERMARKETS

RESTAURANTS

DRYTAC®
ADHESIVE SCIENCE

FloorTac™

Textures

TECHNICAL SPECIFICATION

FloorTac™ Textures is a 6 mil (150µ) printable, matte white phthalate-free polymeric PVC film with a removable, pressure sensitive gray acrylic adhesive protected by a poly coated Kraft release liner. The textured emboss on the film provides slip resistance.

- IDEAL FOR SHORT-TERM INDOOR FLOOR GRAPHICS
- FIRE & SLIP RATED SINGLE PART FLOOR GRAPHIC SOLUTION
- FOR BEST RESULTS, LEAVE A 0.25" (6MM) NON-PRINTED BORDER AROUND THE EDGE OF THE IMAGE.

* Up to 6 months indoor durability dependent upon floor-traffic and correct installation.

INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

PRODUCT STRUCTURE

Film	Textured Matte White Polymeric PVC
Adhesive	Removable Gray Acrylic (Pressure Sensitive)
Release Liner	90# Poly Coated Kraft

PRODUCT CHARACTERISTIC

Film Thickness	6.0 mil (150µ)	7.4 mil (185µ)
Adhesive Layer	1.4 mil (35µ)	
Fire Ratings	Class 1 or A (ASTM E-84) PASS (CAN/ULC-S102)	
Slip Ratings	Moderate Slip Potential (EN 13036-4) Passed (ANSI A137.1/ A326.3) Dry: 58 Wet: 29 (AS HB198:2014 (AS/AZS 4586))	
Application Temperature	>-4˚F (-20˚C)	
Service Temperature Range	-22˚F to 302˚F (-30˚C to 150˚C)	
Shelf Life	2 years	
Storage Conditions	59˚F to 72˚F (15˚C to 22˚C); 50 - 55% Relative Humidity	

PRINTING RECOMMENDATIONS

UV and Latex inks offer the greatest durability for floor applications. Due to the variance of solvent inks it is recommended scuff resistance is tested prior to installation.

DRYTAC®
ADHESIVE SCIENCE

Europe
Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada
30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA
5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013