SpotOn®

SynTac™

ENVIRONMENTALLY FRIENDLY GRAPHICS

This high quality, ink receptive white synthetic paper was specifically developed with the environment in mind. SpotOn® SynTac allows for easy, bubble-free application of vibrant wall and window graphics. SpotOn® SynTac when paired with Interlam™ EcoTex™ creates a two-part environmentally friendly floor graphic solution. SpotOn® SynTac is a printable matte white, self-adhesive PP film with a SpotOn dot pattern, removable pressure sensitive polyacrylate adhesive.

- IDEAL FOR ENVIRONMENTALLY FRIENDLY GRAPHICS
- CAN BE REMOVED EASILY WITHIN 12 MONTHS

Drytac Easy Green Solution

Product Code: SPSF

4.8 mil White Matte PP — Matte

Aqueous Latex UV

DOT Pattern Removable Adhesive

Widths up to 54 in

2 YEARS DURABILITY INTERIOR

6 MONTHS DURABILITY EXTERIOR**



APPLICATIONS

MOUNT TO BOARDS

WINDOW GRAPHICS

FLOOR GRAPHICS*

TEMPORARY SALES SIGNAGE

PRESENTATIONS

POP & EVENT SIGNAGE



2020 Product of the Year
Media – Non-PVC

DRYTAC®
ADHESIVE SCIENCE

SpotOn®

SynTac™

TECHNICAL SPECIFICATION

SpotOn® SynTac™ is a 4.8 mil (120µ) printable matte white, self-adhesive PP film with a dot pattern, removable pressure sensitive polyacrylate adhesive. The adhesive is protected by a single-sided, siliconized Kraft PE coated release liner. This high quality, ink receptive white synthetic paper was specifically developed with the environment in mind. SpotOn® SynTac™ allows for easy, bubble-free application of vibrant graphics.

- IDEAL FOR "ENVIRONMENTALLY FRIENDLY" EASY TO INSTALL GRAPHICS
- GRAPHICS FOR SEASONAL PROMOTIONS APPLICATIONS

*To create a two part PVC-free floor graphic solution, simply pair SpotOn SynTac with Drytac Interlam EcoTex. This pair allows for easy, bubble-free application of vibrant slip-rated floor graphics. SpotOn SynTac paired with Drytac Interlam EcoTex was specifically developed with the environment in mind. SpotOn SynTac is a printable matte white, self-adhesive PP film with a SpotOn dot pattern, removable pressure sensitive polyacrylate adhesive. Interlam EcoTex is PP pressure sensitive overlaminating film with a pebble texture finish. Up to 1 year durability based upon foot traffic and proper installation.

**Please note: ink dependant for outdoor durability.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2021 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

02042021

PRODUCT STRUCTURE

Film	Matte White PP
Adhesive	Removable Dot Pattern Polyacrylate
Release Liner	140 gsm 1 Side Siliconized Kraft with PE coating

PRODUCT CHARACTERISTIC

Film Thickness	4.8 mil (120µ)	5.3 mil (133µ)
Adhesive Layer	0.5 mil (13µ)	
Outdoor Durability	6 months**	
Application Temperature	>41˚F (5˚C)	
Service Temperature Range	-4˚F to 149˚F (-20˚C to 65˚C)	
Shelf Life	1 year	
Storage Conditions	64˚F to 77˚F (18˚C to 25˚C); 40 - 65% Relative Humidity	

DRYTAC®
ADHESIVE SCIENCE

Europe
Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada
30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA
5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013