P
Primers

2.1 VOC Epoxy Primers

Speed Up Your Prime Times!

Features & Benefits:

- 2.1 VOC compliant
- Available in: 274 528SP Gray, 274 530SP White, 274 531SP Black
- Extremely fast dry times
- Corrosion resistant
- Can be applied to properly prepared Stainless Steel and so many other substrates
- Allow 8-12 hours dry time before sanding, if necessary

May be Applied Over:

- Properly cleaned and sanded:
  - Steel/stainless steel
  - Blasted steel
  - Carbon steel
  - Galvanized steel
  - Aluminum
  - Fiberglass
- Previously painted surfaces with proper prep
- MAP® Ultra Low VOC satin or gloss
- MAP®
- SATIN MAP®
- SVOC MAP®
- VOC MAP®
- Body fillers
- Masonry
- Wood



Dry Times at 70°F (21°C):

- Dust Free..... 15 - 20 minutes
- Dry to Touch ..... 20 - 30 minutes
- Dry to Handle..... 30 - 45 minutes
- Dry to Topcoat..... 30 - 45 minutes

mpc MATTHEWS PAINT

The Complete Matthews Paint System:

T Topcoats | P Primers | CLR Clears | CLN Cleaners | A Additives | TR Training

Learn More:
760 Pittsburgh Drive • Delaware, OH 43015
Toll Free: 800.323.6593 • Fax: 800.947.0377
www.matthewspaint.com

mpc PAINT DROPS DESIGN in color is a trademark of PPG Industries Ohio, Inc.
mpc MATTHEWS PAINT and Droplet and Rounded Rectangle is a registered trademark of PPG Industries Ohio, Inc.