

BUILT TO GLOW PACKED TO



Meet a smarter way to package LED modules—designed for speed, simplicity, and less waste.



Module Dimensions L x W x H

Qwik Mod 2 12V (Gen 1)..... 2.2" x 0.69" x 0.25"

Qwik Mod Medium 12V (Gen 2)..... 2.2" x 0.67" x 0.43"

Qwik Mod 2 24V (Gen 2) 2.2" x 0.69" x 0.25"

Reel Dimensions Ø14.0" (flange) x Ø6.75" (barrel) x 12.0" (height)

Beam angle 170°

Mounting options Peel & Stick and mechanical screw hole

Operating temp..... -30° C to +60° C

Environment IP67

Wire color

Qwik Mod 2 12V (Gen 1) & White solid (+) / white w/ black stripe (-)

Qwik Mod Medium 12V (Gen 2)

Qwik Mod 2 24V (Gen 2) White solid (+) / gray solid (-)

Product	Mod/ft	Max. mods (series)*	CCT/ Wavelength	SKU	Power/mod	Intensity	Efficacy	Packaging	Max. mods/60W power supply
Qwik Mod 2 12V Gen 1	1.7	38 mods (22.35 ft)	7100 K	M-QMDX0-71-R	0.80 W	94.1 lm/mod (160 lm/ft)	118 lm/W	Mods per bag: 76 (44.7 ft) Mods per case/reel: 912 (536.52 ft)	76
Qwik Mod Medium 12V Gen 2	1.5	30 mods (20.00 ft)	7100 K	M-QMG2M-12-71-R	0.90 W	126 lm/mod (190 lm/ft)	140 lm/W	Mods per bag: 60 (40.00 ft) Bags per case: 21 Mods per case/reel: 1260 (840.00 ft)	60
			6500 K	M-QMG2M-12-65-R					

Product	Mod/ft	Max. mods (series)*	CCT/ Wavelength	SKU	Power/mod	Intensity	Efficacy	Packaging	Max. mods/96W power supply
Qwik Mod 2 24V Gen 2	1.5	65 mods (44.83 ft)	7100 K	M-QMG22-24-71-R	0.68 W	112 lm/mod (162 lm/ft)	165 lm/W	Mods per bag: 130 (89.66 ft) Bags per case: 10 Mods per case/reel: 1300 (896.55 ft)	130
			6500 K	M-QMG22-24-65-R					

* Max Mods in Series is a NOT a safety requirement; simply a recommendation to ensure even illumination across the strand of modules. Wiring more than the recommended amount in series (up to the FULL power supply load) can result in minimal light loss, but will result in no safety issues.



For more information,
contact **Principal Sloan Customer Service!**

PRINCIPALSLOAN.COM

FIVE BRANDS. ONE MISSION. "We exist to simplify the lives of our customers"

